

JV-SPD01

1/4" Sony Super HAD (Hi-Res) 480TVL/600TVL, Day/Night (IR-Cut Filter Removable, ICR) 23x zoom (10x digital zoom), IP66, built-in Heater & Fan AC 24V.



Features

- 23X Optical/ 10X Digital Zoom
- Auto IRIS & ICR Zoom module
- Digital Slow Shutter (DSS)
- Tilt range 0~90degree, Speed 0.5~120degree/s
- AGC/ ALC/ AES/ BLC/ AWB/ Preset Mask
- RS-485 multi-protocols
- Weather Proof, IP66
- Heater and Blower

JV-SPD01

1/4" Sony Super HAD (Hi-Res) 480TVL/600TVL, Day/Night (IR-Cut Filter Removable, ICR) 23x zoom (10x digital zoom), IP66, built-in Heater & Fan AC 24V.

Specification

SPECIFICATION	JV-SPD01
Video Signal	1.0Vp-p/75Ω(Video 0.714Vp-p / Syc 0.286Vp-p)
Picture Elements	NTSC : 768(H) x 494(V) / PAL : 752(H) x 582(V)
Horizontal Resolution	480 TV Lines
AGC	Auto(24 dB Max)
ALC	Auto / Fix
AES	Auto / Fix
BLC	On / Off
White Balance	ATW / AWB
Optical Zoom	23 x Zoom
Digital Zoom	10 x Zoom
Focus	Auto / Manual
Position	128 Position (Zoom , Focus)
External Control	RS-485
OSD Control	Zoom , Focus , Iris , AWB , AGC , Position , C Gain , APC Gain
Enhancer	Manual H.Gain & V Gain
H/V Reverse	Off / On
Motion Detect	Off / On
Mask	Off / On
Language	English / Chinese / Japanese
Cross Line	Off / On
Freeze	Off / On
Picture Effect	Posi. / Nega
Pan	Pan Range 0~360°, Speed 0.5~260°/S
Tilt	Tilt Range 0 ~ 90°, Speed 0.5~ 120°/S
Preset	128 Preset Positions (Max)
Auto Cruise	1 Auto Cruising Tracks (Max)
Power Source	AC24v / 1.7A
Ambient Temperature	0°C~ 60°C(Recommended 0°C ~ 40°C)
Humidity	10% ~ 90%

Design and specifications are subject to change without notice.