

JV-264-204L

Professional H.264 internet DVR



FEATURES

- Advanced H.264 compression.
- D1 resolution for Preview View and Recording.
- Realtime Live View (120 frame for NTSC, 100 frame for PAL)
- Support 3G cell phone for high quality remote monitoring.
- Visualized Remote Application software.
- Network DDNS/ DHCP function
- 2 USB port/ support USB mouse
- Support Audio/ RS-485/ Sensor
- Advanced Central Management Software

DVR

SPECIFICATION		JV-264-204L	
Video	Video System	NTSC/PAL Switch Selectable	
	Input	BNC x 4 , 1.0Vp-p , 75 ohm	
	Output	BNC x 2, Main output / Spot output	
Audio	VGA output	Option	
	Input	1CH , RCA	
	Output	1CH , RCA	
Control	Mouse	USB/Mouse	
	IR Controller	Yes	
Storage	I / O		
	Build in interface	SATA Hard Disk x1	
Display	Division	1 , 4	
	Zoom	2 x	
Recording	Compression	H.264 (Internet transmission:H.264)	
	Recording Mode	Normal,Manual,Schedule,Alarm,Event	
		Holiday,Sensor	
	Resolution	NTSC	720x480,720x240,360x240(D1/half-D1/CIF)
		PAL	720x576,720x288,360x288(D1/half-D1/CIF)
	Frame Rate	NTSC	30fps(720x480),60fps(720x240) ,120fps(360x240)
	PAL	25fps(720x576),50fps(720x288),100(360x288)	
	Quality	Highest , High , Normal , Low , Lowest	
	Motion Detection	Sensitivity : 15 Level , 16 x 12 Grid	
	Alarm	16 MB	
	Pre-Alarm		
Playback	Speed	Normal , REW & FF(2x / 4x / 8x / 16x / 32x / 64x) , Pause	
	Search Method	Event , Calendar	
Communication	Remote Operation	Visualized AP(The same as Local DVR UI)	
		3G cell phone , CMS , IE Browser	
	Network Communcation	TCP / IP , HTTP , DHCP , ADSL , LAN , DDNS	
	GUI Interface	Supported	
	CMS	Available	
Back up	External	USB 2.0	
	Network	Yes	
	Backup File	H.264 Compression	
General	Unit Dimension	225 x 260 x 50 mm	
	Recovery	Watchdog	
	Operation Temperature	- 5°C ~ 40°C	
	Power Consumption	DC12V , 3.3A , 40W	

