

JV264-204/208/216

Professional H.264 internet DVR



FEATURES

- Advanced H.264 compression.
- D1 resolution for Preview and Recording.
- Realtime Live View (30frame/NTSC, 25frame/PAL)
- Support 3G cell phone for high quality remote monitoring.
- Visualized Remote Application software.
- Provide eSATA port for Storage application.
- Network DDNS/ DHCP function
- Support Audio/ RS-485/ Sensor
- Advanced Central Management Software
- 2 USB port/ support USB mouse

DVR

SPECIFICATION		JV264-204	JV264-208	JV264-216	
Video Input (NTSC/PAL)		4	8	16	
Video Compression		Advanced H.264 Algorithm for saved file and internet transmission			
Video Output		Main output: BNC x1 , Spot output: BNCx1 , VGA x 1 (Option)			
Audio Input		RCA X 4			
Audio Output		RCA X 1			
Sensor In / Alarm Out		4 Sensor in / 1 Alarm out	8 Sensor in / 1 Alarm out	16 Sensor in / 1 Alarm out	
Display	Speed	100/120 fps	200/240 fps	400/480 fps	
	Resolution	720 x 480 (NTSC), 720 x 576 (PAL)			
	Split Screen	1/4/SEQ	1/4/6/8/SEQ	1/4/8/13/16/SEQ	
	Mode	Zoom x 2, PIP, Auto SEQ			
Recording	Resolution (pixels)	NTSC: 720x480, 720x240, 360x240 (D1/Half-D1/CIF) PAL: 720x576, 720x288, 360x288 (D1/Half-D1/CIF)			
	Picture Quality	5 Levels (Highest, High, Normal, Low, Lowest)			
	Mode	Normal, Motion, Alarm, Sensor, Schedule, Holiday, Manual			
	Max Speed	NTSC PAL	120fps(720x240) 100fps(720x288)	240fps(360x240) 200fps(360x288)	480fps(360x240) 400fps(360x288)
	Device	2 internal SATA HDDs or 1 SATA HDD & DVD-RW		3 SATA HDD or 2 SATA HDD & DVD-RW	
Playback	Display	1,4	1,4,8	1,4,8,16	
	Resolution	NTSC PAL	120fps(720x240) 100fps(720x288)	240fps(360x240) 200fps(360x288)	480fps(360x240) 400fps(360x288)
	Search	Segment, Time , Event, Calendar			
	Speed	Normal, REW & FF(2x, 4x, 8x, 16x, 32x, 64x), Pause			
Pre-alarm Recording		16MB (10secs)			
Backup Device		USB 2.0, SATA CD Writer, SATA DVD writer, Remote Network Backup			
PTZ Control		Pelco P, Pelco D, Li-Lin, Dynacolor, LG, Samsung			
Network	Communication	TCP/IP, HTTP, DHCP, ADSL, Lan, DDNS			
	Remote View	IE browser, 3G cell phone (Windows Mobile 5.0/6.0 and Symbian)			
	Remote Operation	Visualized AP(The same as Local DVR UI) , Central management software			
	Users	5 Users allowed to log on DVR simultaneously with independent operation			
Event Notification		Emails (up to 10 setting/ Gmail supported)			
Image format output		H.264			
OSD		GUI (Graphical user interface)			
DVR control		Remote Control, USB Mouse, USB Touch Panel			
Recovery		Watchdog			
Language		Chinese, English, Spanish, Greek, French, Portuguese, Russian, Japanese, German, Italian, Korean, Polish			
Dimension		430x293x55 mm			
Power		External Adaptor, AC100-240V/in, DC12V(5A)			

The Solution to CCTV Security

